

# T7Plus

integrated terminal with high-performance printer









## Lead with the next-generation T7 terminal:

- Delivers fast online authorizations
- One-touch functionality activates wide range of transaction types •
- Eliminates paper jams with drop-in loading SureLoad<sup>™</sup> printer •
- Prints in half the time of previous-generation printers

## CARDSERVICE





www.hypercom.com



integrated terminal with high-performance printer

### **Delivers Fast Authorizations**

The Hypercom<sup>®</sup>, T7 *Plus* builds on the heritage of Hypercom's popular T7 family of terminals. This newest model is designed for merchants requiring a compact countertop POS terminal accepting all magnetic stripe cards and delivering fast online transaction authorizations.

## "The Clam That Won't Jam"

The revolutionary SureLoad<sup>™</sup> printer prints in half the time of previous-generation printers. And it allows paper rolls to simply be dropped in place without feeding through slots and rollers. It also supports longer paper rolls for fewer paper changes and its see-through paper holder alerts cashiers to low conditions before running out of paper in the middle of transactions.

## Supports All Card Types

The T7 Plus supports magnetic stripe cards using a Track 1, 2 reader and is EMV4.0certified. Its 35-key keyboard initiates daily functions and transactions with one simple step and is compatible with previous T7 software, thus reducing certification requirements and training issues.

World Headquarters/ North America Hypercom Corporation 2851 W. Kathleen Road Phoenix, Arizona 85053 USA Tel: +1.602.504.5000 Fax: +1.602.866.5380

Latin America

Hypercom Industria e Comercio LTDA Centro Empresarial Atibaia Rodovia Dom Pedro I, KM 87, 5 Av. Tegula, 888-Ponte Alta Atibaia 12940-000, Brazil Tel: +55.11.4417.7000 Fax: +55.11.4417.7060

Asia/Pacific Rim Hypercom Asia Ltd. 21/F Metro Centre II 21 Lam Hing Street Kowloon Bay, Kowloon Hong Kong Tel: +85.2.2561.6800 Fax: +85.2.2561.5890

Europe/Middle East/Africa Hypercom EMEA, Inc. Unit 2, Woking Eight Forsyth Road Woking, GU21 5SB, United Kingdom Tel: +44.1483.718600 Fax: +44.1483.718601

©2002-2004 Hypercom Corporation, all rights reserved. Hypercom and the Hypercom logo are registered trademarks of Hypercom Corporation. ICE and epicPortz are trademarks of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Hypercom Corporation (NVSE-HYC) is a leading global provider of electronic payment solutions that add value at the point-of-sale for consumers, merchants and acquirers, and yield increased profitability for its customers. Hypercom products include secure, Web-enabled and payment terminals that work seamlessly with its networking equipment and software applications for e-commerce, m-commerce, and and additional payment applications. The company's webly-acquired applications for advantage and acquirers and transfer and acquirers and transfer and acquirers and reaction and acquirers and merce and acquirers and merchants to deverse costs, increase revenues and improve customer retention. Headquartered in Phoenix, Arizona, USA, Hypercom is independently actionated for Hypercom terminals supposed for point-of-sale card payment terminals worldwide. Demand for Hypercom terminals suppassed one million units last year alone. Hypercom today maintains an installed base of more than 6 million card payment terminals in over 100 counties conducting more than 10 billion transactions annually.

**Specifications:** 

#### Keypad

Elastomeric; 35 keys, water-resistant; 3 soft keys (optional); reliable to 500,000 keystrokes (calculated)

#### Display

LCD: 2 lines x 20 characters (standard), 4 lines x 20 characters (optional); backlight reliable to 50,000 hours (calculated)

#### Card Reader

Magnetic stripe: Tracks 1, 2 (standard), Tracks 1, 2, 3 (optional); reliable to 400,000 reads (calculated)

Card Reader Options

IC card interface: non-captive; ISO 7816; EMV-compliant; SIMMLOCK: 4 SAMs

#### Communications

Modem: 56k (optional); 1200, 300 bps (standard); V.22, V.21, synchronous (SDLC) & asynchronous; 2400 bps, V.22 Bis (optional) PIN pad port: 2-wire or 4-wire; RS-422, RS-232 with power or RS-485 2-wire drop LAN & RS-232 without power Peripheral port: compatible with S7C, S7SC, S8, P7E

#### Printer

SureLoad clamshell design, drop-in loading, thermal technology, 384 dots per line, paper roll 57 mm wide x 80 mm diameter

#### Memory

RAM: 512 KB (standard), 1.0 MB (optional) RAM backup: 5-year battery EPROM: 32 KB

Power AC: 85-250 V, 50/60 Hz, DC: 24 V, 1 A

Security Physical: intrusion detector Key management: master/session keys (12) or DUKPT

#### Environment

Temperature: 0-45°C/32-110°F Humidity: max 85%, non-condensing ESD: 12,000 volts

Weight 1.5 lbs/0.68 kg approximate

Footprint 10.0 in x 5.18 in x 2.5 in/25.4 cm x 13.2 cm x 6.35 cm

Product Lifecycle 80,000 hours (calculated), not including printer

Specifications subject to change without notice. 940365-001 Rev C 02/04



innovation. results. leadership.

www.hypercom.com